

I-10A, DLF Industrial Area, Phase-1, Faridabad 121003, Haryana, India

P: +91 9971040808E: info@testronixinstruments.com

Peel Strength / Seal Strength Tester Digital

Adhesion Strength Tester is an innovative instrument which helps in measuring the adhesion Strength or peel ability of self-adhesive pressure sensitive materials. Peel adhesion is defined as the force required to

The Testronix Peel Strength Tester is one of the most popular testing instruments that is used in the packaging and adhesive industries to test the strength of the adhesives.



The instrument consists of two jaws that are used for holding the sample. The specimen is placed between two movable clamps. This applies a force on the sample and peels it off from the surface. The force that is required to peel off the sample from the surface is recorded by the highly accurate load cell given with the equipment. The force applied is displayed on the digital display provided in the machine.





I-10A, DLF Industrial Area, Phase-1, Faridabad 121003, Haryana, India

P: +91 9971040808E: info@testronixinstruments.com

Specification-

- Load Cell Capacity: 20 Kgf
- o Display: LED (Digital)
- \circ Accuracy: $\pm 2\%$ within entire range.
- Least Count/Resolution: 0.020Kgf
- Power: 220V, Single phase, 50 Hz
- $\circ \qquad Speed: 300 \text{ mm/min} \pm 5\%$

Standards – ASTM D429 – 14, ASTM D903

Features-

0	Microprocessor based display for accurate test results
0	Display for Peel Adhesive strength of test specimen
0	Memory to hold up to 9 test reading
0	Strong gripping clamps to perform Peel test at 180 degree.
0	90 degree additional fixture option available (extra cost)
0	Dimensions: 600x500x1120 mm
0	Material: Powder coated mild steel

