

I-10A, DLF Industrial Area, Phase-1, Faridabad 121003, Haryana, India

• P: +91 9971040808

• E : info@testronixinstruments.com

Testronix gloss meter

Testronix's Digital Gloss Meter Tri-angle is a device which is designed specially to measure the gloss reflection on the surface of the material. The instrument is provided with numerous geometrical angles to fulfill the testing need of a vast number of customers. The device is designed specifically to measure the gloss of a particular surface and to ascertain the amount of light which is redirected from the material.



Features

- Measurements of the device are done on the basis of the standards JJG696. The standard fulfills the working requirement of Gloss Meter.
- The chromaticity of the instrument is correspondent to the CIE 1931(2°) which is done under CIE C light source.
- Some Standard Accessories are also delivered with the device which makes the working of the
 instrument easily. The accessories are: Power Adapter, User Manual, USB cable, Calibration
 Plate, and software CD (except basic model) The Device with different geometry degree
 measurements is also available on customer's demand.





I-10A, DLF Industrial Area, Phase-1, Faridabad 121003, Haryana, India

• P: +91 9971040808

• E: info@testronixinstruments.com

Specifications

- It measures 5x36mm area of the sample from 85-degree angle, 9x15mm area at 60-degree angle and 10x10m m area from 20-degree angle.
- The instrument offers the division value of 0.1 GU.
- It provides a measuring range of 0~1000GU from 20 degree, 0~1000GU from 60 degree, 0~160GU from 85 degree.
- The instrument offers different measurement units i.e.
- Range: 100-1000GU, 10-100GU, 0-10GU.
- **Reproducibility**: ± 0.5%GU, ± 0.5GU, ± 0.2GU
- Repeatability: ± 0.2%GU, ± 0.2GU, ± 0.1GU

The instrument is used to measure the brightness, whiteness of the various products such as white sugar and many more and also measure the reflectance of the fabrics when placed in different lighting conditions. It provides great correlation of shining or visual gloss when the sample is placed flat. The correlation of the glass changes if the sample is tilted from the flat position. The procedure is used to measure the shine, appearance, and quality of the products.

The instrument is more suitable to measure the gloss of paints, brightness of paints, opaque glasses, plastics, ceramics, pigments, papers, powders, clothes and many more.

