



Peel Strength / Seal Strength Tester Digital

The Peel Seal Adhesion Strength Tester is an innovative instrument which helps in measuring the adhesion Strength or peel ability of self-adhesive pressure sensitive materials. Peel adhesion is defined as the force required to test the strength of the adhesives.

The instrument consists of two jaws that are used for holding the sample. The specimen is placed between two movable clamps. This applies a force on the sample and peels it off from the surface. The force that is required to peel off the sample from the surface is recorded by the highly accurate load cell given with the equipment. The force applied is displayed on the digital display provided in the machine. This instrument hence can provide the most accurate data analysis so that the manufacturers could provide the best quality to their customers

The Peel Strength Tester is one of the most popular testing instruments that is used in the packaging and adhesive industries to test the strength of the adhesives. The following tests can be conducted on one single instrument:

- 1. Adhesive strength test
- 2. Peel strength tester
- 3. Seal strength test
- 4. Bond strength test

The instrument complies with various tester standards such as Standards – ASTM D429 – 14, ASTM D903 Available models: Peel/adhesion/bond/seal strength tester Computerized

MODEL NO. TX-PBT 200





Safety Limit Switches



Push for Burst



Microprocessor **Based Digital Display**

(e) +91-9313140140

info@testronixinstruments.com

www.testronixinstruments.com







FEATURES

- Microprocessor based display for accurate test results
- Display for Peel Adhesive strength of test specimen
- Memory to hold up to 9 test reading
- Strong gripping clamps to perform Peel test at 180 degree.
- Dimensions: 600x500x1120 mm
- Material: Powder coated mild steel

Optional and additional accessories:

- 1. Computerized model
- 2. Speed drive for accurate results
- 3. 90 degree fixture

SPECIFICATION



- Load Cell Capacity: 20 Kgf
- Display: LED (Digital)
- Accuracy: $\pm 0.5\%$ within entire range.
- Least Count/Resolution: 0.002Kgf
- Power: 220V, Single phase, 50 Hz
- Speed: 300 mm/min±5%

Thank you customers for choosing us as your partners in growth !



*All the above logos are the sole property of their respective owners and are used purely for depiction purposes only.

OUR OTHER PRODUCTS :-



- (e) +91-9313140140
- info@testronixinstruments.com
- www.testronixinstruments.com

